



MANUEL D'UTILISATION ET D'ENTRETIEN

LES TALOCHEUSES

MODELES
B90/B436 ET B120/B446

NOTA: INDIQUEZ LE MODELE ET LE NUMERO DE SERIE POUR COMMANDER LES PIECES D'ETACHEES.



PUISSANCE - EFFICACITE - FAIBILITE

375 ANNAGEM BLVD., MISSISSAUGA, ONTARIO, CANADA, L5T 3A7, 905-364-4200 FAX 905-364-4201
25 INDUSTRIAL DRIVE, KEYPORT, NEW JERSEY, USA, 07735, 732-566-6400 FAX 732-566-5444

Doc. # OI-B09001
Orig. Rel. - 07-2004
Curr. Rev. - 01
Rev. Date - 08-2012

**MANUEL D'UTILISATION ET D'ENTRETIEN LES TALOCHEUSES
SPECIFICATIONS**

WALK-BEHIND TROWEL

Model	Path	Power Source (gas option)	Float Blade Size	Finish Trowel Size	Combination Blade Size	Pans Floats	Pans Floats	Operating Weight
B436	36" (90 cm)	5.5 hp Honda OHV 9 hp Honda OHV	10" x 14" (25 x 36 cm)	6" x 14" (15 x 36 cm)	8" x 14" (20 x 36 cm)	38 ½" (98 cm)	186 lbs. 85 kg	Up to 165 lb. (75 kg)
B446	46" (120 cm)	9 hp Honda OHV 9 hp Robin OHV 11 hp Honda OHV 11 hp Robin OHV	10" x 18" (25 x 46 cm)	6" x 18" (15 x 46 cm)	8" x 18" (20 x 46 cm)	48 ½" (123 cm)	187 lbs. 85 kg	Up to 245 lb. (110 kg)

Walk Behind Trowel (GASOLINE)	
Blade Speed (RPM)	130-160
Engine Speed (RPM)	3600
Clutch Type	Centrifugal
Variable Speed	Yes
Gearbox Oil	Agma 8 compounded gear oil
Gearbox Oil Capacity	16 oz. (473 ml), 19 oz. (562 ml)
Engine Fuel	Gasoline – Unleaded
Engine Oil Alert	Yes
Cooling	Air
Starting	Recoil Starter - Manual
Dead-man Safety Switch	Yes
Fuel Capacity (approximately)	3 Gal. (12.5 L)
Running Time (approximately)	2 ½ hours
Number of Blades	4
Engine Acoustic Power Lwa (dB)	97-103
Engine Acoustic Pressure Lpa (Db)	82-86
Level of Vibration	1.1-1.5
Vibration value on the handle	7.0 aw
Options	Oil-Bath Spider Assembly Insta-Pitch Lever Hoist Hook Carry Bar Folding Handle

- Power rating conforming to DIN 6270 & ISO 3048/1 Std.
- RPM results may vary by engine option.